



Main

Commercial Status	Commercialised
Range of product	KNX
Product or component type	Control unit 0-10 V
Operating mode	KNX bus system Manual operation
Bus type	KNX

Complementary

Total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V AC, 50...60 Hz
Input current	0.12...100 mA
Analogue output type	Voltage
Analogue output range	1...10 V
Number of outputs	3
[In] rated current	16 A
Load type	Capacitive: , 16 A, 200 µF, 100...240 V AC Parallel compensated fluorescent lamp: ≤ 2608 VA, 240 V AC Parallel compensated fluorescent lamp: ≤ 2500 VA, 230 V AC Parallel compensated fluorescent lamp: ≤ 1086 VA, 100 V AC Halogen lamps: ≤ 2608 W, 240 V AC Halogen lamps: ≤ 2500 W, 230 V AC Halogen lamps: ≤ 1086 W, 100 V AC Incandescent lamps: ≤ 3840 W, 240 V AC Incandescent lamps: ≤ 3600 W, 230 V AC Incandescent lamps: ≤ 1600 W, 100 V AC

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(YYWW)	0830

Contractual warranty

Period	18 months
--------	-----------